

Medical AC-DC Adapter

VPS-030AAC Series / VPS-030AAC□

030AAC



Highlights & Features

- VPS-030AAC05, 12, 15, 24 Meet DOE Level VI & ErP 2017
- Low touch current. Suitable for type BF applications
- Detachable AC plug with multiple country options
- Class B EMI and 4th Edition Immunity Compliant
- Safety rated for medical and IT applications
- IP22 ingress protection rating
- 2 × MOPP isolation
- 500K hours MTBF
- 3 years warranty

Safety Standards



CB Certified for worldwide use

Model Number: VPS-030AAC□
Unit Weight: 150 grams
Dimensions (W × L × H): 53.5 × 88.0 × 27.5 mm
 2.11 × 3.46 × 1.08 inch

General Description

The VPS series of external power supply comes with universal AC input at 85Vac to 264Vac. Other features include low touch current, risk management report available and the electric shock protection comply with 2 × MOPP. The VPS series is certified for EMC standards according to EN 55011 for industrial, scientific and medical (ISM) radio-frequency equipment and EN 55022 for Information Technology Equipment (ITE) radio-frequency equipment. In addition, only recognized Japanese capacitors are used.

The VPS series come with both medical and ITE safety approvals including UL/cUL and IEC-60950-1 CB certification as a Limited Power Source (LPS), and CCC approval. Designs are fully compliant with RoHS Directive 2011/65/EU for environmental protection.

Model Information

Medical AC-DC Adapter

Model Number	Input Voltage Range	Efficiency Level	Rated Output Voltage	Rated Output Current
VPS-030AAC05	85-264Vac	Level VI	5Vdc	3A
VPS-030AAC07		Level V	7Vdc	3A
VPS-030AAC12		Level VI	12Vdc	2A
VPS-030AAC15		Level VI	15Vdc	2A
VPS-030AAC24		Level VI	24Vdc	1.25A

Model Numbering

VPS –	030	AAC	□	AA
Power Supply	Max wattage in the product series (may be lower at some voltage)	Family Code	Output Voltage (Single Output) - 05 for 5V - 15 for 15V - 07 for 7V - 24 for 24V - 12 for 12V	Revision Code ^{1), 2)}

1) 1st digit: DC plug type and output cable length. A for 2.1 × 5.5 × 10 mm DC plug, and 1200 mm cable length.
 2) 2nd digit: Country duck-head type (A_ China, B_ United States, C_ European, D_ United Kingdom, E_ Australia, G_ Korea, H_ India, J_ Argentina, K_ Brazil, M_ South Africa)

All parameters are specified at 25°C ambient unless otherwise indicated.

Medical AC-DC Adapter

VPS-030AAC Series / VPS-030AAC□

Specifications

Model Number	VPS-030AAC05	VPS-030AA07	VPS-030AAC12	VPS-030AAC15	VPS-030AAC24
--------------	--------------	-------------	--------------	--------------	--------------

Input Ratings / Characteristics

Nominal Input Voltage	100-240Vac					
Input Voltage Range	85-264Vac					
Nominal Input Frequency	50-60Hz					
Input Frequency Range	47-63Hz					
Input Current (max)	115Vac	0.5A	0.6A	0.8A	0.8A	0.8A
	230Vac	0.3A	0.4A	0.6A	0.6A	0.6A
Average Efficiency (min)	115Vac	81.4%	81.4%	86.21%	87.0%	87.0%
	230Vac	81.4%	81.4%	86.21%	87.0%	87.0%
Standby Power (max)	115Vac	0.1W	0.1W	0.1W	0.1W	0.1W
	230Vac	0.1W	0.1W	0.1W	0.1W	0.1W
Inrush Current (typ.)	60A @ 115Vac and 230Vac					
Touch Current (max)	0.1mA @ 264Vac NC ¹⁾ , 0.3mA @ 264Vac SFC ²⁾					
Output-PE (protective earth) leakage current for Type BF application (max)	0.1mA @ 264Vac NC ¹⁾ , 0.5mA @ 264Vac SFC ²⁾					

- 1) NC: Normal condition
- 2) SFC: Single fault condition


Model Number	VPS-030AAC05	VPS-030AA07	VPS-030AAC12	VPS-030AAC15	VPS-030AAC24
--------------	--------------	-------------	--------------	--------------	--------------

Output Ratings / Characteristics

Nominal Output Voltage	5Vdc	7Vdc	12Vdc	15Vdc	24Vdc
Output Voltage Tolerance	±1%				
Output Current	3A	3A	2A	2A	1.25A
Output Power	15W	21W	24W	30W	30W
Line Regulation	±1%				
Load Regulation	±5%				
Ripple & Noise (max)	100mVpk-pk @ Rated load	100mVpk-pk @ Rated load	150mVpk-pk @ Rated load	200mVpk-pk @ Rated load	200mVpk-pk @ Rated load
Start-up Time (max)	3000ms @ 115Vac				
Hold-up Time (min)	10ms @ 115Vac				
Dynamic Response (Overshoot & Undershoot O/P Voltage)	±10% @ 50-100% load				
Capacitive load (max)	4700uF				

*Periodic and Random Deviation.

Ripple & Noise measurement circuit with 20MHz BW



All parameters are specified at 25°C ambient unless otherwise indicated.



Medical AC-DC Adapter

VPS-030AAC Series / VPS-030AAC

Specifications	Model Number	VPS-030AAC05	VPS-030AA07	VPS-030AAC12	VPS-030AAC15	VPS-030AAC24
----------------	--------------	--------------	-------------	--------------	--------------	--------------

Mechanical

Case Chassis	PC	
Case Cover	PC	
Dimensions (W × L × H)	53.5 × 88.0 × 27.5 mm (2.11 × 3.46 × 1.08 in)	
Unit Weight	150 grams (5.3 ounces)	
Indicator	NA	
Cooling System	NA	
Terminal	Input	Detachable type AC plug
	Output	Barrel type. Dimensions 2.1 × 5.5 × 10 mm (see page 5)

Environment

Surrounding Air Temperature	Operating	0°C to +40°C
	Storage	-40°C to +85°C
Operating Humidity	5 - 95% RH (Non-Condensing)	
Operating Altitude	5,000 meters (16400 feet)	
Shock Test (Non-Operating)	50G, 11ms, 3 shocks for each direction	
Vibration (Operating)	5-500Hz, 2.09Grms, 20 minute for each three axis	

Protections

Overvoltage (max)	150%, Latch Mode
Overload / Overcurrent (max)	250% of rated load current, Hiccup Mode, (Non-Latching, Auto-Recovery)
Over Temperature	Hiccup Mode, (Non-Latching, Auto-Recovery)
Short Circuit	Hiccup Mode, (Non-Latching, Auto-Recovery)
Degree of Protection	IP22
Protection Against Shock	Class II

Reliability Data

MTBF (min)	500K Hours based on Telecordia SR-332 (at 100Vac, Max. load and 25°C Ambient)
------------	---

All parameters are specified at 25°C ambient unless otherwise indicated.



Medical AC-DC Adapter

VPS-030AAC Series / VPS-030AAC

Specifications	Model Number	VPS-030AAC05	VPS-030AA07	VPS-030AAC12	VPS-030AAC15	VPS-030AAC24
----------------	--------------	--------------	-------------	--------------	--------------	--------------

Safety Standards / Directives

Medical Safety	IEC 60601-1 Edition 3.1 (2012), EN60601-1 (2006) + A11 + A1 + A12, CAN/CSA-C22.2 NO. 60601-1:14, ANSI/AAMI ES60601-1:2005/(R)2012	
ITE Safety	IEC60950-1 (Ed.2,2005), GB4943.1-2011, GB9254-2008, GB17625.1-2003	
CE	MDD Directive 93/42/EEC	
Material and Parts	RoHS Directive 2011/65/EU Compliant	
Galvanic Isolation	Input to Output	4000 Vac

EMC

EMC / Emissions	EN55011/EN55022,FCC Title 47:Class B	
Harmonic Current Emissions	IEC61000-3-2	Meet Class A limit
Immunity to	EN 55024, EN 61000-6-1, EN 55014-2	
Voltage Flicker	IEC61000-3-3	
Radiated Field	IEC61000-4-2	Level 4 Criteria A ^{1), 4)} Air Discharge: 15kV Contact Discharge: 8kV
Radiated Field	IEC60601-1-2	Level 3 Criteria A ¹⁾ 80MHz-1000GHz, 10V/m AM modulation Criteria A ^{1), 4)} 80MHz-2700MHz, 10V/m AM modulation 385MHz-5785MHz, 28V/m Pulse mode and other modulation
Electrical Fast Transient / Burst	IEC61000-4-4	Level 3 Criteria A ¹⁾ : 2kV
Surge	IEC61000-4-5	Level 3 Criteria A ^{1), 4)} Differential Mode ³⁾ : 1kV
Conducted	IEC61000-4-6	Level 2 Criteria A ^{1), 4)} 150kHz-80MHz, 3Vrms, 6Vrms at ISM bands and Amateur radio bands
Power Frequency Magnetic Fields	IEC61000-4-8	Criteria A ^{1), 4)} Magnetic field strength 30A/m
Voltage Dips	IEC61000-4-11	30% 10ms Criteria A ¹⁾ 60% 100ms Criteria B ²⁾ 100% 5000ms Criteria B ²⁾
Voltage Dips	IEC60601-1-2	Criteria B ^{2), 4)} 30% 500ms Criteria A ¹⁾ 100% 10ms at step: 45 degree Criteria B ²⁾ 100% 20ms Criteria B ²⁾ 100% 5000ms

1) Criteria A: Normal performance within the specification limits

2) Criteria B: Output out of regulation, or shuts down during test. Automatically restore to normal operation after test.

3) Symmetrical: Differential mode (Line to line)


4) Compliant with IEC-60601-1-2 4th edition requirements.

All parameters are specified at 25°C ambient unless otherwise indicated.

Medical AC-DC Adapter


VPS-030AAC Series / VPS-030AAC □

Block Diagram



Dimensions

W × H × H: 53.5 × 88.0 × 27.5 mm
























Note:
The plug's polarity is

Medical AC-DC Adapter

VPS-030AAC Series / VPS-030AAC

Duck Head Type:

AU type	BZ type	EU type
  	  	  

UK type	CN type	US/JP type	KR type
  	  	  	  

Medical AC-DC Adapter

VPS-030AAC Series / VPS-030AAC

Functions

Start-up Time

The time required for the output voltage (V_o) to reach 90% of its set value, after the input AC voltage is applied.


Rise Time

The time required for the output voltage (V_o) to change from 10% to 90% of its steady state value.

Hold-up Time


Hold up time is the time when the AC input collapses and output voltage retains regulation for a certain period of time. The time required for the output to reach 95% of its set value, after the input voltage is removed.

■ Graph illustrating the Start-up Time, Rise Time, and Hold-up Time




Inrush Current

Inrush current is the input current that occurs when the input voltage is first applied. For AC input voltages, the maximum peak value of inrush current will occur during the first half cycle of the applied AC voltage. This peak value decreases exponentially during subsequent cycles of AC voltage.



Dynamic Response

The power supply output voltage will remain within $\pm 3\%$ of its steady state value, when subjected to a dynamic load change from 50 to 100% of its rated current.




All parameters are specified at 25°C ambient unless otherwise indicated.

Medical AC-DC Adapter

VPS-030AAC Series / VPS-030AAC

Overload & Over current Protections

The power supply's Overload (OLP) and Over current (OCP) Protections will be activated when output current is between 110% and 130% of I_O (Max load). Upon such an occurrence, V_O will start to drop. Once the power supply has reached its maximum power limit, the protection will be activated and the power supply will go into "Hiccup mode" (Auto-Recovery). The power supply will recover once the fault condition causing the OLP and OCP is removed and I_O is back within the specified limit.



Additionally, if the I_O is <130% but >110% for a prolonged period of time (depending on the load), the Over Temperature Protection (OTP) will be activated due to high temperature on critical components. The power supply will then go into hiccup mode until the fault is removed; and, the input voltage is removed, then reapplied.

Short Circuit Protection (Auto-Recovery)

The power supply's output OLP/OCP function also provides protection against short circuits. When a short circuit is applied, the output current will operate in "Hiccup mode", as shown in the illustration in the OLP/OCP section on this page. The power supply will return to normal operation after the short circuit is removed.

All parameters are specified at 25°C ambient unless otherwise indicated.

Overvoltage Protection

The power supply's overvoltage circuit will be activated when its internal feedback circuit fails. The output voltage shall not exceed its specifications defined on Page 3 under "Protections". Power supply will hiccup mode, and require removal/re-application of input AC voltage in order to restart.

Over Temperature Protection

As mentioned above, the power supply also has Over Temperature Protection (OTP). This is activated when the overload condition persists for an extended duration and the output current is below the overload trigger point but >100% load. In the event of a higher operating condition at 100% load, the power supply will run into OTP when the surrounding air temperature is higher than the operating temperature. When activated, the output voltage will go into hiccup mode until the input voltage is removed; then, reapplied, and the surrounding air temperature drops to its normal operating temperature.