

SPS-1230/1820/2415/3610/606



FEATURES

- * Dual Measurement Display
- * 0.01 % High Regulation
- * Constant Voltage and Constant Current
 Operation
- * High Efficiency
- * High Power Density
- * Over Voltage Protection
- * Remote Output ON/OFF Control

Rear Panel





The SPS-Series are single output, 360W, switching DC power supply OVP protects the SPS-Series and their load from unexpected conditions. High regulation is maintained at 0.01%. Remote sensing adds extra level of precision by compensating cable losses between loads. Turning the output On/Off from external device is available through Remote control terminals. The GPS-Series are an ideal solution for power-efficient bench-top or portable applications requiring high regulation.

| SPECIFICATIONS | | | | | | | |
|--|---|---|----------|----------|---------|--|--|
| OUTPUT | | | | | | | |
| | SPS-1230 | SPS-1820 | SPS-2415 | SPS-3610 | SPS-606 | | |
| Voltage | 0 ~ 12V | 0 ~ 18V | 0 ~ 24V | 0 ~ 36V | 0 ~ 60V | | |
| Current | 0 ~ 30A | 0 ~ 20A | 0 ~ 15A | 0 ~ 10A | 0 ~ 6A | | |
| CONSTANT VOLTAGE OPERATION | | | | | | | |
| Regulation | Line regulation ≤5mV | | | | | | |
| | Load regulation ≤5mV | | | | | | |
| Ripple & Noise | ≤5mVrms, 100mVp-p 20Hz ~ 20MHz | | | | | | |
| Recovery Time | ≤500μS | | | | | | |
| | (50% Load change, Minimum load 0.5A) | | | | | | |
| Temp. Coefficient | ≤ 100ppm / °C | | | | | | |
| Output Range | 0 to rating vo | 0 to rating voltage continuously adjustable | | | | | |
| CONSTANT CURRENT OP | ERATION | | | | | | |
| Regulation | Line regulation ≤3mA | | | | | | |
| | Load regulation ≤3mA | | | | | | |
| Ripple Current | ≤3mArms (SPS-606) | | | | | | |
| | ≤5mArms (SPS-3610) | | | | | | |
| | ≤10mArms (SPS-2415) | | | | | | |
| | ≤10mArms (SPS-1820) | | | | | | |
| | ≤30mArms (SPS-1230) | | | | | | |
| Output Range | 0 to rating current continuously adjustable | | | | | | |
| . • | (HI/LO range switchable) | | | | | | |
| METER | | | | | | | |
| Type 3 1/2 digit, 0.39" LED display | | | | | | | |
| Accuracy | \pm (0.5% of rds | (0.5% of rdg + 2digits) | | | | | |
| INSULATION | | | | | | | |
| Chassis and Terminal | 20M Ω or above (DC 500V) | | | | | | |
| Chassis and AC Cord | 30MΩ or abo | $30 M\Omega$ or above (DC 500V) | | | | | |
| POWER SOURCE | | | | | | | |
| AC 115V/ 230V \pm 15 %, 50/ | 60Hz | | | | | | |
| DIMENSIONS & WEIGHT | | | | | | | |
| 128(W) x 151(H) x 295(D) mm, Approx. 3.2kg | | | | | | | |

| | | ORDERING | INFORMATION | | |
|------|----------------------------------|----------------------------------|-------------|--|--|
| SPS- | -1230 | 360W D.C. Switching Power Supply | | | |
| SPS- | -1820 | 360W D.C. Switching Power Supply | | | |
| SPS- | -2415 | 360W D.C. Switching Power Supply | | | |
| SPS- | -3610 | 360W D.C. Switching Power Supply | | | |
| SPS | -606 | 360W D.C. Switching Power Supply | | | |
| ACC | ACCESSORIES : | | | | |
| User | User manual x 1 , Power cord x 1 | | | | |
| Test | Test lead GTL-203 x 1 | | | | |