



Your Power House
VP ELECTRONIQUE

3310G Series DC Electronic Load

	Normal mode		Turbo mode
3310G	60V / 30A / 150W	➔	60V / 60A / 300W
3311G	60V / 60A / 300W	➔	60V / 120A / 600W
3312G	250V / 12A / 300W	➔	250V / 24A / 600W
3314G	500V / 12A / 300W	➔	500V / 24A / 600W
3315G	60V / 15A / 75W	➔	60V / 30A / 150W
3316G	80V / 80A / 400W	➔	80V / 160A / 800W
3318G	500V / 20A / 400W	➔	500V / 40A / 800W



Features

- 5 digital V / A / W Meter can be displayed on Large LCD display simultaneously.
- Flexible CC, CR, CV, CP, CC + CV, CP + CV, Dynamic and short circuit operation modes.
- Built-in test modes include Battery Discharge, BMS, Fuse/Breaker Trip/Non-Trip, Short circuit, OCP, OPP test modes.
- Not only CC, CR, and CP mode have parallel operation functions, but CV mode also has parallel operation functions.
- Turbo mode can withstand up to 2 times the current and power electronic load within 2 sec. period, most fit Fuse/Breaker and BMS, Short circuit, OCP, OPP test.
- Provide battery BMS protection test function.
- High Slew Rate : 3310G up to 5A/uS, 3311G up to 10A/uS, 3315G up to 2.5A/uS
- Support MPPT CC, CR, CV test function for solar panel.
- Short circuit duration can be set within short circuit test.
- Can set the power-on status value.
- Voltage meter display can be configured as polarity positive ("+") or negative ("-").
- Synchronous parallel execution function (SYNC. Load on)
- Can be configured in the Mainframe of 3302G (single channel), 3305G (dual channels) or 3300G (Quad channels), each mainframe has up to 150 sets Store/Recall memory.
- Optional programmable NTC Resistor (installed in mainframe)
- Optional Interface : GPIB, RS232, USB, LAN.
- Protection against V, I, W, and °C.
- Optional 9923 load current waveform generator to provide the battery actual discharge current waveform simulation.

Descriptions

- Each 3310G Series module has its own control and display panel, CC/CR/CV/CP/Dynamic modes, plug in 3302G/3305G/3300G mainframe with 150 sets Store/Recall memory which provides load set-up more efficiently, also can be controlled via RS232, Ethernet, USB and GPIB interface.
- The new Turbo mode is designed for overload or protection testing, which includes OCP, OPP, Short for AC/DC or DC/DC power source; Over Charge/Discharge and Short for Battery BMS protection; and Blow/Not Blow testing for Fuse, Breaker or PTC Current Protection Components.
- Support Short, OCCP and OCDP protection tests for battery BMS protection testing, the peak current before protection and protection response time are measured.
- BMS, Fuse, OCP and OPP single-key test functions on the module make test more efficient.
- Dynamic can be simulated under CC, CP mode. The current Rise / Fall slew rate can be adjusted individually and there is an external signal input so that load can have a simulated Specific Load Current Waveform, optional 9923 Load Current Waveform Generator is able to support real current waveform testing.
- SHORT duration setting and SHORT_VH, SHORT_VL setting function, also can measure Short Voltage and Current.
- Programmable LOAD ON/OFF voltage, GO/NG meter check, Voltage meter display "+" or "-" is selectable and 150 sets Store / Recall larger memory is much advance feature for each different application.
- 150 sets test parameter and status storage function can call the storage memory real time in accordance with the auto sequence requirement, at any time to tune out the stored memory for use.

Applications

- Voltage / Current source SMPS transient response
- Voltage Source Current limit testing and battery emulation for Charger testing
- Battery discharge capacity
- Lithium battery BMS charge and discharge protection
- Fuse, Breaker, PTC specification test
- MPPT test function for solar panels
- R&D, Quality Control
- ATE system
- Production testing

Specifications

MODEL	3310G		3311G		3312G		3314G		3315G		
Power	150W, 300W max. ^{*1}		300W, 600W max. ^{*1}		300W, 600W max. ^{*1}		300W, 600W max. ^{*1}		75W, 150W max. ^{*1}		
Current	30A, 60A max. ^{*1}		60A, 120A max. ^{*1}		12A, 24A max. ^{*1}		12A / 24A max. ^{*1}		15A / 30A max. ^{*1}		
Voltage	60V		60V		250V		500V		60V		
Min. Operating Voltage	0.3V @ 30A		0.3V @ 60A		1V @ 12A		6V @ 12A		0.25V @ 15A		
PROTECTIONS											
Over Power Protection(OPP)					105%						
Over Current Protection(OCP)					105%						
Over Voltage Protection(OVP)					105%						
Over Temp Protection(OTP)					YES						
Constant Current Mode											
Range ^{*2}	0 ~ 3A	0 ~ 30A	0 ~ 6A	0 ~ 60A	0 ~ 1.2A	0 ~ 12A	0 ~ 1.2A	0 ~ 12A	0 ~ 1.5A	0 ~ 15A	
Resolution	0.05mA	0.5mA	0.1mA	1mA	0.02mA	0.2mA	0.02mA	0.2mA	0.0254mA	0.25mA	
Accuracy	± 0.05% of (setting + Range)										
Constant Resistance Mode											
Range	2~120KΩ	0.02Ω~2Ω	1Ω~60 KΩ	0.0083Ω~1Ω	25Ω~1500KΩ	0.08Ω~25Ω	50 ~ 3000KΩ	0.5Ω ~ 50Ω	4Ω ~ 240 KΩ	0.02Ω ~ 4Ω	
Resolution	0.00833mS	0.033mΩ	0.0166mS	0.0166mΩ	0.00066mS	0.4166mΩ	0.000333mS	0.8333mΩ	0.04166mS	0.0666mΩ	
Accuracy	± 0.2% of (Setting + Range)										
Constant Voltage Mode											
Range	0 ~ 6V	0 ~ 60V	0 ~ 6V	0 ~ 60V	0 ~ 30V	0 ~ 250V	0 ~ 60V	0 ~ 500V	0 ~ 6V	0 ~ 60V	
Resolution	0.0001V	0.001V	0.0001V	0.001V	0.001V	0.01V	0.001V	0.01V	0.0001V	0.001V	
Accuracy	± 0.025% of (Setting + Range)										
Constant Power Mode											
Range	0 ~ 15W	0 ~ 150W	0 ~ 30W	0 ~ 300W	0 ~ 30W	0 ~ 300W	0 ~ 30W	0 ~ 300W	0 ~ 7.5W	0 ~ 75W	
Resolution	0.00025W	0.0025W	0.0005W	0.005W	0.0005W	0.005W	0.001W	0.01W	0.000125W	0.00125W	
Accuracy	± 0.1% of (Setting + Range)										
Constant Current + Constant Voltage Mode											
Range	60V	30A	60V	60A	250V	12A	500V	12A	60V	15A	
Resolution	0.001V	0.5mA	0.001V	1mA	0.01V	0.2mA	0.01V	0.2mA	0.001V	0.25mA	
Accuracy	± 1.0% of (Setting + Range)										
Constant Power + Constant Voltage Mode											
Range	60V	150W	60V	300W	250V	300W	500V	300W	60V	75W	
Resolution	0.001V	0.0025W	0.001V	0.005W	0.01V	0.005W	0.01V	0.01W	0.001V	0.00125W	
Accuracy	± 1.0% of (Setting + Range)										
Maximum Current	Turbo OFF Turbo ON ^{*1}	30A 60A	60A 120A	12A 24A	12A 24A	12A 24A	15A 30A	15A 30A	15A 30A	15A 30A	
Meas. Accuracy	± 1.0% of (Reading + Range)										
Short/OCP/OPP Test Function											
Short Time	Turbo OFF Turbo ON ^{*1}	100ms~10 Sec. or Continue 100~2000ms									
Meas. Accuracy	NA										
OCP Time (Tstep)	Turbo OFF Turbo ON ^{*1}	100mS 20mS									
Meas. Accuracy	NA										
OPP Time (Tstep)	Turbo OFF Turbo ON ^{*1}	100mS 20mS									
Meas. Accuracy	NA										
BMS Test Mode ^{*3}											
Short Time	Turbo OFF Turbo ON ^{*1}	0.05mS~10ms 0.05mS~10ms									
Meas. Accuracy	±0.005mS										
OCP Time (Tstep)	Turbo OFF Turbo ON ^{*1}	0.05mS~10ms / 11~1000ms 0.05mS~10ms / 11~1000ms									
Meas. Accuracy	±0.005mS / ±0.2mS										
Fuse Test Mode ^{*4}											
Trip & Non-Trip Time	Turbo OFF Turbo ON ^{*1}	r1 : 1~5999ms, r2 : 6~16383sec 1~2000mS									
Meas. Accuracy	r1 : ±0.2mS(<200mS), ±20mS(>200mS), r2: ±0.5S										
Repeat Cycle	0~255										
Surge Test Mode											
Surge current	0~60A		0~120A		0~24A		0~24A		0~30A		
Normal current	0~30A		0~60A		0~12A		0~12A		0~15A		
Surge Time	10~2000ms										
Surge Step	1~5										
MPPT Mode											
Algorithm	P & O										
Load mode	CV										
P&O interval	1000ms ~ 60000ms										
Dynamic Mode (50KHz)											
Timing											
Thigh & Tlow	0.010~9.999 / 99.99 / 999.9 / 9999mS										
Resolution	0.001 / 0.01 / 0.1 / 1mS										
Slew rate	0.008~0.5A/uS	0.08~5A/uS	0.016~1A/uS	0.16~10A/uS	0.0008~0.05A/uS	0.008~0.5A/uS	0.0008~0.05A/uS	0.008~0.5A/uS	0.004~0.25A/uS	0.04~2.5A/uS	
Accuracy	± (5% of Setting) ±10uS										
Measurement											
Voltage Read Back											
Range (5 Digital)	6V	60V	6V	60V	30V	250V	60V	600V	6V	60V	
Resolution	0.0001V	0.001V	0.0001V	0.001V	0.001V	0.01V	0.001V	0.01V	0.0001V	0.001V	
Accuracy	± 0.025% of (Reading + Range)										
Current Read Back											
Range (5 Digital)	3A	30A	6A	60A	1.2A	12A	1.2A	30A	1.5A	15A	
Resolution	0.0001A	0.001A	0.0001A	0.001A	0.00002A	0.0002A	0.0001A	0.01A	0.00001A	0.001A	
Accuracy	± 0.05% of (Reading + Range)										
Power Read Back											
Range (5 Digital)	15W	150W	30W	300W	30W	300W	30W	300W	7.5W	75W	
Resolution	0.001W	0.01W	0.001W	0.01W	0.001W	0.01W	0.001W	0.01W	0.0001W	0.001W	
Accuracy	± 0.1% of (Reading + Range)										
Current Monitor	FULL SCALE 10V										
Accuracy	0.5% of (Setting + Range)										
Current Programming Input	FULL SCALE 10V										
Programmable Short	BUILT-IN										
Load ON Voltage	0.1 ~ 25V	0.1 ~ 25V		0.2 ~ 50V		0.4 ~ 100V		0.1 ~ 25V			
Accuracy	1% of (Setting + Range)										
Load OFF Voltage	0 ~ 25V	0 ~ 25V		0 ~ 50V		0 ~ 100V		0 ~ 25V			
Accuracy	0.025% of (Setting + Range)										
Typical Short Resistance	0.0086 Ω		0.0043 Ω		0.08 Ω		0.5 Ω		0.0129Ω		
Maximum Short Current	30 A		60A		12A		12A		15A		
Dimension(HxWxD)	143 x 108 x 412 mm										
Operating Temperature ^{*5}	0 ~ 40°C										

*1 : Up to 2 times rated current and power @1/3 voltage rating Turbo mode operation for Fuse, BMS, Short / OCP / OPP testing. *4 : Fuse test function is mainly used for fuse and breaker testing

*2 : CC Mode can be forced on Range II

*3 : The BMS test function is mainly applied to the Short / OCP / OPP and OCPD tests of the battery BMS protection board.

*5 : The operating temperature range is 0~40°C, the accuracy of this specification is only applicable to 25°C±5°C

Order Information

DC Electronic Load

- ▶ 3310G 60V, 30A, 150W
- ▶ 3311G 60V, 60A, 300W
- ▶ 3312G 250V, 12A, 300W
- ▶ 3314G 500V, 12A, 300W



DC Electronic Load Mainframe

- ▶ 3302G (single channel mainframe) 5.5kg / W160mm / H177mm / D452mm
- ▶ 3305G (two channels mainframe) 7.5kg / W269mm / H177mm / D452mm
- ▶ 3300G (four channels mainframe) 9.3kg / W440mm / H177mm / D445mm

Optional interface : ① GPIB Card ② RS232 Card ③ USB Card ④ LAN Card
Optional feature : NTC Simulator ① 10KΩ NTC(100~500KΩ) ② 100KΩ NTC(1000~5MΩ)

High Slew Rate

- 3310G ▶ 5A/uS
- 3311G ▶ 10A/uS
- 3315G ▶ 2.5A/uS

Specifications

MODEL	3316G		3318G	
Power	400W, 800W max. ^{*1}		400W, 800W max. ^{*1}	
Current	80A / 160A max. ^{*1}		20A / 40A max. ^{*1}	
Voltage	80V		500V	
Min. Operating Voltage	0.8V @ 80A		4V @ 20A	
PROTECTIONS				
Over Power Protection(OPP)			105%	
Over Current Protection(OCP)			105%	
Over Voltage Protection(OVP)			105%	
Over Temp Protection(OTP)			YES	
Constant Current Mode				
Range ^{*2}	0 ~ 8.04A	0 ~ 80.4A	0 ~ 2.04A	0 ~ 20.4A
Resolution	0.134mA	1.34mA	0.034mA	0.34mA
Accuracy	± 0.05% of (setting + Range)			
Constant Resistance Mode				
Range	1Ω~ 60KΩ	0.0083Ω ~ 1Ω	30Ω~ 1800KΩ	0.3Ω ~ 30Ω
Resolution	0.0166mS	0.0166mΩ	0.000555mS	0.5mΩ
Accuracy	± 0.2% of (Setting + Range)			
Constant Voltage Mode				
Range	0 ~ 8.04V	0 ~ 80.4V	60V	500V
Resolution	0.000134V	0.00134V	0.001V	0.01V
Accuracy	± 0.025% of (Setting + Range)			
Constant Power Mode				
Range	0 ~ 40.02W	0 ~ 400.2W	0 ~ 40.02W	0 ~ 400.2W
Resolution	0.667mW	6.67mW	0.667mW	6.67mW
Accuracy	± 0.1% of (Setting + Range)			
Constant Current + Constant Voltage Mode				
Range	80V	80A	500V	20A
Resolution	0.00134V	1.34mA	0.01V	0.34mA
Accuracy	± 1.0% of (Setting + Range)			
Constant Power + Constant Voltage Mode				
Range	80V	400W	500V	400W
Resolution	0.00134V	6.67mW	0.01V	6.67mW
Accuracy	± 1.0% of (Setting + Range)			
Maximum Current	Turbo OFF Turbo ON ^{*1}	80A 160A	20A 40A	
Meas. Accuracy	± 3.0% of (Reading + Range)			
Short/OCP/OPP Test Function				
Short Time	Turbo OFF Turbo ON ^{*1}	100ms~10 Sec. or Continue 100~2000ms		
Meas. Accuracy	NA			
OCP Time (Tstep)	Turbo OFF Turbo ON ^{*1}	100mS 20mS		
Meas. Accuracy	NA			
OPP Time (Tstep)	Turbo OFF Turbo ON ^{*1}	100mS 20mS		
Meas. Accuracy	NA			
BMS Test Mode^{*3}				
Short Time	Turbo OFF Turbo ON ^{*1}	0.05mS~10ms 0.05mS~10ms		
Meas. Accuracy	±0.005mS			
OCP Time (Tstep)	Turbo OFF Turbo ON ^{*1}	0.05mS~10ms / 11~1000ms 0.05mS~10ms / 11~1000ms		
Meas. Accuracy	±0.005mS / ±0.2mS			
Fuse Test Mode^{*4}				
Trip & Non-Trip Time	Turbo OFF Turbo ON ^{*1}	r1 : 1~5999ms, r2 : 6~16383sec 1~2000mS		
Meas. Accuracy	r1 : ±0.2mS(<200mS), ±20mS(>200mS), r2: ±0.5S			
Repeat Cycle	0~255			
Surge Test Mode				
Surge current	0~160A		0~40A	
Normal current	0~80A		0~20A	
Surge Time	10~2000ms			
Surge Step	1~5			
MPPT Mode				
Algorithm	P&O			
Load mode	CV			
Dynamic Mode (50KHz)				
Timing				
Thigh & Tlow	0.010~9.999 / 99.99 / 999.9 / 9999mS			
Resolution	0.001 / 0.01 / 0.1 / 1mS			
Slew rate	5.4 ~ 337.5mA/us	54~ 3375mA/us	1.28 ~ 80mA/us	12.8 ~ 800mA/us
Accuracy	± (5% of Setting) ±10uS			
Measurement				
Voltage Read Back				
Range (5 Digital)	8.04V	80.4V	60V	500V
Resolution	0.000134V	0.00134V	0.001V	0.01V
Accuracy	± 0.025% of (Reading + Range)			
Current Read Back				
Range (5 Digital)	8.04A	80.4A	2.04A	20.4A
Resolution	0.000134A	0.00134A	0.000034A	0.00034A
Accuracy	± 0.05% of (Reading + Range)			
Power Read Back				
Range (5 Digital)	100W	400W	100W	400W
Resolution	0.001W	0.01W	0.001W	0.01W
Accuracy	± 0.1% of (Reading + Range)			
Current Monitor	FULL SCALE 10V			
Accuracy	0.5% of (Setting + Range)			
Current Programming Input	FULL SCALE 10V			
Programmable Short	BUILT-IN			
Load ON Voltage	0.1 ~ 25V		0.4~100V	
Accuracy	1% of (Setting + Range)			
Load OFF Voltage	0 ~ 25V		0~100V	
Accuracy	0.025% of (Setting + Range)			
Typical Short Resistance	0.009Ω		0.15Ω	
Maximum Short Current	80A		20A	
Dimension(HxWxD)	143 x 108 x 412 mm			
Operating Temperature ^{*5}	0 ~ 40°C			

*1 : Up to 2 times rated current and power @1/3 voltage rating Turbo mode operation for Fuse, BMS, Short / OCP / OPP testing. *4 : Fuse test function is mainly used for fuse and breaker testing
 *2 : CC Mode can be forced on Range II *5 : The operating temperature range is 0~40°C, the accuracy of this specification is only applicable to 25°C±5°C
 *3 : The BMS test function is mainly applied to the Short / OCP / OPP and OCPD tests of the battery BMS protection board.

Order Information

DC Electronic Load

- ▶ 3316G
80V · 80A · 400W
- ▶ 3318G
500V · 20A · 400W



DC Electronic Load Mainframe

- ▶ 3302G
(single channel mainframe)
5.5kg / W160mm / H177mm / D452mm
- ▶ 3305G
(two channels mainframe)
7.5kg / W269mm / H177mm / D452mm
- ▶ 3300G
(four channels mainframe)
9.3kg / W440mm / H177mm / D445mm



Optional interface : ① GPIB Card ② RS232 Card ③ USB Card ④ LAN Card

