



Your Power House
VP ELECTRONIQUE

EC-0122


VPE75W Series

Half-Brick DC-DC converter up to 75 Watts

3
YEARS
WARRANTY

ROHS
COMPLIANT

REACH
COMPLIANT



cULus CB CE

3000
VAC
Reinforced
Insulation

3000
VDC
Isolation
Voltage

4 : 1
Wide
Input
Range

NO
Min. Load
Required

REMOTE
ON
OFF

OCP

OTP

OVP

SCP

UVP

PART NUMBER STRUCTURE

DIP Type:

VPE75	-	48	S	05	W	-	P	HS
Series Name		Input Voltage (VDC)	Output Quantity	Output Voltage (VDC)	Input Range		Ctrl and Pin Options	Assembly Options
		24:9~36 48:18~75 110:43~160	S:Single	3P3:3.3 05:5 12:12 15:15 24:24 28:28 48:48	4:1		□:Negative logic; 0.20" pin length L:Negative logic; 0.145" pin length P:Positive logic; 0.20" pin length S:Positive logic; 0.145" pin length	□: None Heat-sink type HS: 7G-0021A-F; H=0.45" HS1: 7G-0022A-F; H=0.24" HS2: 7G-0023A-F; H=0.24" HS3: 7G-0024A-F; H=0.45" HS4: 7GA0127P01-F; H=0.65" HS5: 7GA0128P01-F; H=1" Through hole type TH: No thread*
*The module can't equip Heat-sink with TH option.								

Wall Mounted Type:

VPE75	-	48	S	05	W	-	P	TF1	R
Series Name		Input Voltage (VDC)	Output Quantity	Output Voltage (VDC)	Input Range		Ctrl and Pin Options	Assembly Options	Conformal Coating Options
		24:9~36 48:18~75 110:43~160	S:Single	3P3:3.3 05:5 12:12 15:15 24:24 28:28 48:48	4:1		□:Negative logic; 0.20" pin length P:Positive logic; 0.20" pin length	T: Without EMC filter TF1: Integrated EMC filter and meets EN55032 Class A can be connected to PE	□: None R: Conformal Coating

1. The terminal block type is only for assembly of 0.20 "pin length.

2020.10.19

TECHNICAL SPECIFICATION All specifications are typical at nominal input, full load and 25°C unless otherwise noted

Model Number	Input Range	Output Voltage	Output Current @Full Load	Input Current @ No Load	Efficiency	Maximum Capacitor Load
	VDC	VDC	A	mA	%	μF
VPE75-24S3P3W	9 ~ 36	3.3	20	85	87	60600
VPE75-24S05W	9 ~ 36	5	15	120	88	30000
VPE75-24S12W	9 ~ 36	12	6.3	185	88	5250
VPE75-24S15W	9 ~ 36	15	5	185	88	3330
VPE75-24S24W	9 ~ 36	24	3.2	85	87	1330
VPE75-24S28W	9 ~ 36	28	2.7	85	87	960
VPE75-24S48W	9 ~ 36	48	1.6	85	87	330
VPE75-48S3P3W	18 ~ 75	3.3	20	60	88	60600
VPE75-48S05W	18 ~ 75	5	15	60	90	30000
VPE75-48S12W	18 ~ 75	12	6.3	90	90	5250
VPE75-48S15W	18 ~ 75	15	5	50	89	3330
VPE75-48S24W	18 ~ 75	24	3.2	50	88	1330
VPE75-48S28W	18 ~ 75	28	2.7	50	88	960
VPE75-48S48W	18 ~ 75	48	1.6	50	87	330
VPE75-110S3P3W	43 ~ 160	3.3	20	10	89	60600
VPE75-110S05W	43 ~ 160	5	15	10	91	30000
VPE75-110S12W	43 ~ 160	12	6.3	10	91	5250
VPE75-110S15W	43 ~ 160	15	5	10	91	3330
VPE75-110S24W	43 ~ 160	24	3.2	10	90	1330
VPE75-110S28W	43 ~ 160	28	2.7	10	90	960
VPE75-110S48W	43 ~ 160	48	1.6	10	90	330

INPUT SPECIFICATIONS								
Parameter	Conditions			Min.	Typ.	Max.	Unit	
Operating input voltage range		24Vin(nom)		9	24	36	VDC	
		48Vin(nom)		18	48	75		
		110Vin(nom)		43	110	160		
Start up voltage		24Vin(nom)				9	VDC	
		48Vin(nom)				18		
		110Vin(nom)				43		
Shutdown voltage		24Vin(nom)		7.3	7.7	8.1	VDC	
		48Vin(nom)		15.5	16	16.3		
		110Vin(nom)		33.0	34.5	36.0		
Start up time	Constant resistive load	Power up	110Vin(nom)			60	ms	
			Others			25		
		Remote ON/OFF	110Vin(nom)			60		
Input surge voltage	1 second, max.		Others			25	VDC	
		24Vin(nom)				50		
		48Vin(nom)				100		
		110Vin(nom)				185		
Input filter ⁽¹⁾					Pi type			
Remote ON/OFF	Referred to –Vin pin	Negative logic	DC-DC ON			Short or 0 ~ 1.2VDC		
		(Standard)	DC-DC OFF					Open or 3 ~ 12 VDC
		Positive logic	DC-DC ON					Open or 3 ~ 12 VDC
		(Option)	DC-DC OFF					Short or 0 ~ 1.2VDC
		Input current of Ctrl pin		-0.5	1	mA		
		Remote off input current			3	mA		

OUTPUT SPECIFICATIONS

Parameter	Conditions	Min.	Typ.	Max.	Unit
Voltage accuracy		-1.0		+1.0	%
Line regulation	Low Line to High Line at Full Load	-0.1		+0.1	%
Load regulation	No Load to Full Load	-0.1		+0.1	%
Voltage adjustability	Maximum output deviation is inclusive of remote sense	-20		+10	%
Remote sense	% of Vout(nom) If remote sense is not being used, Sense pins should be connected to corresponding polarity OUTPUT pins.			10	%
Ripple and noise	Measured by 20MHz bandwidth With a 4.7µF/50V X7R MLCC 3.3Vout, 5Vout With a 4.7µF/50V X7R MLCC 12Vout, 15Vout With a 4.7µF/50V X7R MLCC 24Vout, 28Vout With a 2.2µF/100V X7R MLCC 48Vout		75 100 200 300	100 125 250 350	mVp-p
Temperature coefficient		-0.02		+0.02	%/°C
Transient response recovery time	25% load step change		200	250	µs
Over voltage protection	% of Vout(nom); Hiccup mode	115		130	%
Over load protection	% of Iout rated; Hiccup mode 110Vin(nom) Others		150		%
Short circuit protection		110		140	
		Continuous, automatic recovery			

GENERAL SPECIFICATIONS

Parameter	Conditions	Min.	Typ.	Max.	Unit
Isolation voltage	1 minute(Reinforced insulation) 110Vin(nom) Input to Output Input (Output) to Case	3000 1500			VAC
	1 minute Others Input to Output Input (Output) to Case	3000 1600			VDC
Isolation resistance	500VDC	1			GΩ
Isolation capacitance				2500	pF
Switching frequency		270	300	330	kHz
Safety approvals	IEC/ EN/ UL62368-1			UL:E193009 CB:UL(Demko)	
Standard approvals	EN50155 EN45545-2				
Case material	24Vin(nom) and 48Vin(nom) 110Vin(nom)				Metal Aluminum base-plate with plastic case
Base material	24Vin(nom) and 48Vin(nom)				FR4 PCB
Potting material					Silicone (UL94 V-0)
Weight	Module stand alone HAE75-□□S□□W -T HAE75-□□S□□W -TF1			97g (3.42oz) 200g (7.05oz) 287g (10.12oz)	
MTBF	MIL-HDBK-217F, Full load				3.362×10 ⁵ hrs

ENVIRONMENTAL SPECIFICATIONS

Parameter	Conditions	Min.	Typ.	Max.	Unit
Operating case temperature	Base-plate	-40		+105	°C
Maximum case temperature				105	°C
Over temperature protection			115		°C
Storage temperature range	Terminal block type	-40		+105	°C
	Others	-55		+125	
Thermal impedance	Module without assembly options Heat-sink type with 0.24" Height Heat-sink type with 0.45" Height Heat-sink type with 0.65" Height Heat-sink type with 1" Height		6.7 5.4 4.7 3.7 3.0		°C/W
Thermal shock					MIL-STD-810F
Shock					EN61373, MIL-STD-810F
Vibration					EN61373, MIL-STD-810F
Relative humidity					5% to 95% RH


EMC SPECIFICATIONS		
Parameter	Conditions	Level
EMI	EN55011, EN55032 VPE75-□□S□□W-TF1 Other models; with external components *Connecting four screw bolts to shield plane will help to reduce the EMI.	Class A Class A, Class B
ESD	EN61000-4-2 Air ± 8kV and Contact ± 6kV	Perf. Criteria A
Radiated immunity	EN61000-4-3 20V/m	Perf. Criteria A
Fast transient	EN61000-4-4 ± 2kV VPE75-24S□□W VPE75-48S□□W With 2 pcs of aluminum electrolytic capacitor (Nippon Chemi-con KY series, 220µF/100V) VPE75-110S□□W With 2 pcs of aluminum electrolytic capacitor (Nippon Chemi-con KXJ series, 150µF/200V)	Perf. Criteria A
Surge	EN61000-4-5 EN55024 ±2kV and EN50155 ±2kV VPE75-24S□□W VPE75-48S□□W With 2 pcs of aluminum electrolytic capacitor (Nippon Chemi-con KY series, 220µF/100V) VPE75-110S□□W With 2 pcs of aluminum electrolytic capacitor (Nippon Chemi-con KXJ series, 150µF/200V)	Perf. Criteria A
Conducted immunity	EN61000-4-6 10Vr.m.s	Perf. Criteria A
Power frequency magnetic field	EN61000-4-8 100A/m continuous; 1000A/m 1 second	Perf. Criteria A

Note:


- Input source impedance: The power module will operate as specifications without external components, assuming that the source voltage has a very low impedance and reasonable input voltage regulation. Highly inductive source impedances can affect the stability of the power module. Since real-world voltage source has finite impedance, performance can be improved by adding external filter capacitor. The VPE75-24S□□W recommended 4.7µF/50V X7R MLCC or Nippon Chemi-con KY series, 68µF /100V or better capacitor.

CAUTION: This power module is not internally fused. An input line fuse must always be used.


CHARACTERISTIC CURVE




VPE75-48S05W Derating Curve
(See Thermal Considerations)



VPE75-48S05W Efficiency vs. Input Voltage



VPE75-48S05W Derating Curve with Heat-sink
(See Thermal Considerations)



VPE75-48S05W Efficiency vs. Output Load

FUSE CONSIDERATION

This power module is not internally fused. An input line fuse must always be used.

This encapsulated power module can be used in a wide variety of applications, ranging from simple stand-alone operation to an integrated part of sophisticated power architecture.

To maximum flexibility, internal fusing is not included; however, to achieve maximum safety and system protection, always use an input line fuse.


The input line fuse suggest as below :

Model	Fuse Rating (A)	Fuse Type
VPE75-24S □□W	15	Fast-Blow
VPE75-48S □□W	8	Fast-Blow
VPE75-110S □□W	3.15	Slow-Blow

The table based on the information provided in this data sheet on inrush energy and maximum DC input current at low Vin.

MECHANICAL DRAWING


VPE75-24S□□W, VPE75-48S□□W



BOTTOM VIEW

■ The screw locked torque: MAX 5.0kgf-cm/0.49N-m

VPE75-110S□□W



BOTTOM VIEW

- The screw locked torque: MAX 3.5kgf-cm/0.34N-m

PIN CONNECTION

PIN	DEFINE	DIAMETER
1	-Vin	0.04 Inch
2	Case	0.04 Inch
3	Ctrl	0.04 Inch
4	+Vin	0.04 Inch
5	-Vout	0.08 Inch
6	-Sense	0.04 Inch
7	Trim	0.04 Inch
8	+Sense	0.04 Inch
9	+Vout	0.08 Inch

1. All dimensions in inch [mm]
2. Tolerance :x.xx±0.02 [x.x±0.5]
x.xxx±0.01 [x.xx±0.25]
3. Pin dimension tolerance ±0.004[0.10]




Your Power House
VP ELECTRONIQUE

EC-0122

VPE75W Series

TERMINAL BLOCK TYPE OPTION

VPE75-□□S□□W -T




TERMINAL CONNECTION : -T

NO.	DEFINE
1	-Vin
2	Case / NC*
3	Ctrl
4	+Vin
5	-Vout
6	-Sense
7	Trim
8	+Sense
9	+Vout

1. All dimensions in inch [mm]
2. Tolerance :x.xx±0.02 [x.x±0.5]
x.xxx±0.01 [x.xx±0.25]
3. Screw 1 locked torque:
MAX 11.2kgf-cm/ 1.10N-m
4. Screw 2 locked torque:
MAX 5.2kgf-cm/ 0.51N-m
5. Screw 3 locked torque:
MAX 12.0kgf-cm/ 1.18N-m


VPE75-□□S□□W -TF1



TERMINAL CONNECTION : -TF1

NO.	DEFINE
1	-Vin
2	NC
3	Ctrl
4	+Vin
5	-Vout
6	-Sense
7	Trim
8	+Sense
9	+Vout

RECOMMENDED PAD LAYOUT



All dimensions in inch[mm]
 Pad size(lead free recommended)
 Through hole 1,2,3,4,6,7,8: $\Phi 0.051$ [1.30]
 Through hole 5,9: $\Phi 0.091$ [2.30]
 Through hole of mounting: $\Phi 0.126$ [3.20]
 Top view pad 1,2,3,4,6,7,8: $\Phi 0.064$ [1.63]
 Top view pad 5,9: $\Phi 0.113$ [2.88]
 Top view pad of mounting: $\Phi 0.157$ [4.00]
 Bottom view pad 1,2,3,4,6,7,8: $\Phi 0.102$ [2.60]
 Bottom view pad 5,9: $\Phi 0.181$ [4.60]
 Bottom view pad of mounting: $\Phi 0.252$ [6.40]

THERMAL CONSIDERATIONS

The power module operates in a variety of thermal environments.

However, sufficient cooling should be provided to help ensure reliable operation of the unit.

Heat is removed by conduction, convection, and radiation to the surrounding Environment.


Proper cooling can be verified by measuring the point as the figure below.

The temperature at this location should not exceed "Maximum case temperature".

When Operating, adequate cooling must be provided to maintain the test point temperature at or below "Maximum case temperature".

You can limit this Temperature to a lower value for extremely high reliability.


- Thermal test condition with vertical direction by natural convection (20LFM).
- The Heat-sink is optional and P/N: 7G-0021A-F, 7G-0022A-F, 7G-0023A-F, 7G-0024A-F, 7GA0127P01-F, 7GA0128P01-F.



BASE PLATE


HEAT-SINK TYPE OPTIONS

VPE75-□□S□□W -HS
7G-0021A-F




SIDE VIEW

VPE75-□□S□□W -HS1
7G-0022A-F




SIDE VIEW

VPE75-□□S□□W -HS2
7G-0023A-F




SIDE VIEW

VPE75-□□S□□W -HS3
7G-0024A-F




SIDE VIEW

VPE75-□□S□□W -HS4
7GA0127P01-F



SIDE VIEW

VPE75-□□S□□W -HS5
7GA0128P01-F



SIDE VIEW

1. All dimensions in inch [mm]
2. Tolerance :x.xx±0.02 [x.x±0.5]
x.xxx±0.01 [x.xx±0.25]

OUTPUT VOLTAGE ADJUSTMENT

Output voltage is adjustable for 10% trim up or -20% trim down of nominal output voltage by connecting an external resistor between the Trim pin and either the +Sense or -Sense pins.

With an external resistor between the Trim and -Sense pin, the output voltage set point decreases.

With an external resistor between the Trim and +Sense pin, the output voltage set point increases.

Maximum output deviation is +10% inclusive of remote sense.

The external TRIM resistor needs to be at least 1/8W of rated power.

■ Trim Up Equation

$$R_U = \left(\frac{V_{OUT}(100 + \Delta\%) - 100 + 2\Delta\%}{1.225\Delta\%} \right) k\Omega$$


■ Trim Down Equation

$$R_D = \left(\frac{100}{\Delta\%} - 2 \right) k\Omega$$

EXTERNAL OUTPUT TRIMMING

Output can be externally trimmed by using the method shown below.

Trim-up



□□S3P3W

ΔV (%)	1	2	3	4	5	6	7	8	9	10
Vout (V)	3.333	3.366	3.399	3.432	3.465	3.498	3.531	3.564	3.597	3.630
RU (k Ω)	170.082	85.388	57.156	43.041	34.571	28.925	24.892	21.867	19.515	17.633

□□S05W

ΔV (%)	1	2	3	4	5	6	7	8	9	10
Vout (V)	5.05	5.10	5.15	5.20	5.25	5.30	5.35	5.40	5.45	5.50
RU (k Ω)	310.245	156.163	104.803	79.122	63.714	53.442	46.105	40.602	36.322	32.898

□□S12W

ΔV (%)	1	2	3	4	5	6	7	8	9	10
Vout (V)	12.12	12.24	12.36	12.48	12.60	12.72	12.84	12.96	13.08	13.20
RU (k Ω)	887.388	447.592	300.993	227.694	183.714	154.395	133.452	117.745	105.528	95.755

□□S15W

ΔV (%)	1	2	3	4	5	6	7	8	9	10
Vout (V)	15.15	15.30	15.45	15.60	15.75	15.90	16.05	16.20	16.35	16.50
RU (k Ω)	1134.735	572.490	385.075	291.367	235.143	197.660	170.886	150.806	135.188	122.694

□□S24W

ΔV (%)	1	2	3	4	5	6	7	8	9	10
Vout (V)	24.24	24.48	24.72	24.96	25.20	25.44	25.68	25.92	26.16	26.40
RU (k Ω)	1876.776	947.184	637.320	482.388	389.429	327.456	283.190	249.990	224.168	203.510

□□S28W


ΔV (%)	1	2	3	4	5	6	7	8	9	10
Vout (V)	28.28	28.56	28.84	29.12	29.40	29.68	29.96	30.24	30.52	30.80
RU (k Ω)	2206.571	1113.714	749.429	567.286	458.000	385.143	333.102	294.071	263.714	239.429

□□S48W

ΔV (%)	1	2	3	4	5	6	7	8	9	10
Vout (V)	48.48	48.96	49.44	49.92	50.40	50.88	51.36	51.84	52.32	52.80
RU (k Ω)	3855.551	1946.367	1309.973	991.776	800.857	673.578	582.665	514.480	461.447	419.020

OUTPUT VOLTAGE ADJUSTMENT(CONTINUED)

Trim-down



□□S□□W

ΔV (%)	1	2	3	4	5	6	7	8	9	10
RD (k Ω)	98.000	48.000	31.333	23.000	18.000	14.667	12.286	10.500	9.111	8.000
ΔV (%)	11	12	13	14	15	16	17	18	19	20
RD (k Ω)	7.091	6.333	5.692	5.143	4.667	4.250	3.882	3.556	3.263	3.000