



Your Power House
VP ELECTRONIQUE

8500 Series

Programmable AC Power Source

The EEC 8500 Series is the most power dense and functionality rich source in EEC history, giving you improved capability, functionality, and a reduced footprint in one series. These new models provide an output voltage of up to 310 VAC and an output frequency ranging from 5 Hz - 1,200 Hz, making it the obvious solution for all kinds of applications. Configure this power source as a simple bench top AC Power Source in Manual mode or, as an upgraded option, Advanced mode, to be used with an interface to a PC. The 8500 Series includes the following models: 8505, 8512, 8520, 8530, 8540, 8560



Features

- 14 pre-configured waveforms allow you to simulate nearly any abnormal condition on your DUT by simply selecting the waveform you would like to output.
- With expanded output voltage to 310VAC and output frequency from 5Hz to 1200Hz, the 8500 provides a single, simple solution to meet a wide variety of testing applications.
- Advanced mode option allows you to easily simulate voltage surges, voltage drops, voltage pulses, voltage sweeps, DC bias, and frequency sweeps to help make meeting the specific needs of your testing application easier than it has ever been.
- High power density with a reduced overall footprint offers you the flexibility you need to use your 8500 Series power source in either a bench top or rack mount application.
- Easily upgrade and keep your command set from your 6000, 7000, or 300XAC Series with the legacy program mode.



Applicable Industries



Aerospace



Appliance



Laboratory



Networking



System Integrator



Lighting



Medical

EEC Benefits



Standard

USB/RS-232 Interface

Ethernet Interface

Options

GPIB Interface





Modes

INPUT	STANDARD MODE	ADVANCED MODE
Manual Operation	•	•
PC Interface (USB/LAN standard, optional GPIB)		•
PowerTRAC Compatibility		•
Voltage, Frequency, Transient, and DC Bias Sweeps		•

Specifications – 8500

8500 SPECIFICATIONS							
MODEL		8505	8512	8520	8530	8540	8560
AC OUTPUT							
Phase		1Ø2W					
Power Rating		500VA	1250VA	2kVA	3kVA	4kVA	6kVA
Voltage	Range	0 - 310V, 155/310V Auto Range					
	Resolution	0.1V					
	Accuracy	±(0.2% of setting + 3counts)				±(0.2% of setting + 6counts)	
Max. Current (r.m.s) ¹	0 - 155V	5A	12.5A	20A	30A	40A	60A
	0 - 310V	2.5A	6.25A	10A	15A	20A	30A
Frequency	Range	DC, 5 - 1200Hz Full Range Adjust					
	Resolution	0.1Hz at 0.0 - 999.9Hz , 1Hz at 1000 - 1200Hz					
	Accuracy ²	±0.03% of setting(≥ 15Hz) , ±0.3% of setting(<15Hz)					
Total Harmonic Distortion (THD) ³		≤ 0.3% @ 50/60Hz (Full Resistive Load)					
Crest Factor ⁴		≥ 3	≥ 3	≥ 3	2.5	≥ 3	2.5
Inrush Current		4	4	4	3	4	3
Line Regulation		± 0.1V					
Load Regulation ⁵		±0.2V,<1s response time					
DC OUTPUT							
Power rating		300W	750W	1200W	1800W	2400W	3600W
Voltage	Range	0 - 420V, 210/420V Auto Range					
	Resolution	0.1V					
	Accuracy	±(0.2% of setting + 3counts)			±(0.2% of setting + 6counts)		
Max. Current (r.m.s) ²	0 - 210V	3.0A	7.5A	12.0A	18.0A	24.0A	36.0A
	0 - 420V	1.5A	3.75A	6.0A	9.0A	12.0A	18.0A
Ripple and Noise (r.m.s) ⁶	Range	L	< 700mV			< 800mV	
		H	< 700mV			< 800mV	
Ripple and Noise (p-p) ⁶		< 6.0Vp-p			< 7.0Vp-p		
Load Regulation ⁵		±0.2V,<1s response time					



Specifications – 8500

8500 SPECIFICATIONS							
MODEL		8505	8512	8520	8530	8540	8560
SETTINGS							
Start/End Angle	Range	0-359					
	Resolution	1					
Current Hi Limit (OC Fold=OFF) OC Fold Back (OC Fold=ON)	0 - 155V	0.05-5.00A	0.05-12.50A	0.05-20.00A	0.10-30.00A	0.10-40.00A	0.10-60.00A
	0 - 310V	0.05-2.50A	0.05-6.25A	0.05-10.00A	0.10-15.00A	0.10-20.00A	0.10-30.00A
	Resolution	0.01A					
	Accuracy	± (2.0% of setting + 4 counts)					
OC Fold Back Response Time ⁷		< 1.4s					
Time	Range	1.0 - 999.9h/ 1.0 - 999.9m /1.0 - 999.9s /0.2 - 999.9ms					
	Resolution	0.1h/ 0.1m/ 0.1s/ 0.1ms					
	Accuracy	± (0.1% + 0.1 h)/ ± (0.1% + 0.1 m)/ ± (0.1% + 0.1 s)/ ± (0.1% + 0.1 ms)					
Time unit		h, m, s, ms					
Ramp up	Range	0.1 - 999.9s, 0 = OFF					
	Resolution	0.1s					
	Accuracy	± (0.1% + 1 Cycle) at Output frequency ≤ 10Hz/ ± (0.1% + 0.1 s) at Output frequency > 10Hz					
INPUT							
Phase		1Ø					1Ø or 3Ø
Voltage		100 - 240 V ± 10%			200 - 240 V ± 10%		1Ø/3Ø3W: 200-240V±10% 3Ø4W: 346 - 416V ± 10%
Max. Current		8A	18A	30A	22A	30A	1Ø :45A/3Ø3W: 38A 3Ø4W: 22A
Frequency		50 / 60 Hz					
Power Factor ⁸		≥ 0.93	≥ 0.97				

Specifications – 8500

8500 SPECIFICATIONS													
MODEL	8505		8512		8520		8530		8540		8560		
MEASUREMENT													
Voltage(AC)	Range		0 - 310V, 155/310V Auto Range										
	Resolution		0.1V										
	Accuracy ²		±(0.2% of reading + 3counts) at voltage > 5V					±(0.2% of reading + 6counts) at voltage > 5V					
Voltage(DC)	Range		0 - 420V, 210/420V Auto Range										
	Resolution		0.1V										
	Accuracy ²		±(0.2% of reading + 3counts) at voltage > 5V					±(0.2% of reading + 6counts) at voltage > 5V					
Current ⁹	Range	L	0.050 - 1.200A		0.050 - 5.000A			-					
		Resolution	1.00 - 6.25A		4.00 - 15.62A		4.00 - 25.00A		0.10 - 37.50A		0.10 - 50.00A		0.10 - 75.00A
	Resolution ³	L	0.001A					-					
		H	0.01A										
	Accuracy ²	L	± (1% of reading + 10counts) at CF < 3					-					
		H	± (0.5% of reading +8counts)					± (0.5% of reading +12counts)					
Frequency	Range		0.0 - 1200Hz										
	Resolution		0.1Hz / 1Hz										
	Accuracy		±0.1Hz @ 5 - 999.9Hz. / ±1Hz @ 1000 - 1200Hz										
Power ¹⁰ (AC,DC)	Range	L	0.0 - 75.0W		0.0 - 300.0W			-					
		H	60 - 625W		240 - 1563W		240 - 2500W		0 - 3750W		0 - 5000W		0 - 7500W
	Resolution	L	0.1W					-					
		H	1W										
	Accuracy	L	± (1% of reading +10 counts) at PF ≥ 0.35 and voltage > 5V		± (2% of reading +15 counts) at PF ≥ 0.35 and voltage > 5V			-					
		H	± (1% of reading +5 counts) at PF ≥ 0.35 and voltage > 5V		± (1% of reading +10 counts) at PF ≥ 0.35 and voltage > 5V			± (1% of reading +20 counts) at PF ≥ 0.35 and voltage > 5V					
Power Factor	Range		0.000 - 1.000										
	Resolution		0.001										
	Accuracy		W/VA, Calculated and displayed to three significant digits										
Power Apparent (VA)	Range	L	0.0 - 75.0VA		0.0 - 300.0VA			-					
		H	60 - 625VA		240 - 1563VA		240 - 2500VA		0 - 3750VA		0 - 5000VA		0 - 7500VA
	Resolution	L	0.1VA					-					
		H	1VA										
Calculated Formula		$\sqrt{V \times A}$, Calculated value											
Peak Current Measurement	Range		0.0 - 20.0Apk		0.0 - 50.0Apk		0.0 - 80.0Apk		0.0 - 120.0Apk		0.0 - 160.0Apk		0.0 - 240.0Apk
	Resolution		0.1A										
	Accuracy		± (0.5% of reading +8counts)					± (0.5% of reading +12counts)					
Reactive Power Measurement	Range	L	0.0 - 75.0VAR		0.0 - 300.0VAR			-					
		H	60 - 625VAR		240 - 1563VAR		240 - 2500VAR		0 - 3750VAR		0 - 5000VAR		0 - 7500VAR
	Resolution	L	0.1VAR					-					
		H	1VAR										
Calculated Formula		$\sqrt{(VA)^2 - (AP)^2}$, Calculated value											
Crest Factor Measurement	Range		0.00 - 10.00										
	Resolution		0.01										
	Accuracy		Ap / A										



Specifications – 8500

8500 SPECIFICATIONS						
MODEL	8505	8512	8520	8530	8540	8560
GENERAL						
PLC Remote Control	Input:Output ON, Output OFF/Reset, Output Verify, Interlock,File Recall M1 through M7, Trigger Output: Fail, Test-in-Process					
Rear Input	AC Outlet	Terminal Block				
Memory	Std.	10 x 100 (file x sequence) / MANUAL only 10 file no sequence				
	Adv.	100 x 100 (file x sequence) / MANUAL, STEP, PULSE only 100 file no sequence				
Sync Signal/ Ext Trigger	Std.	ON/OFF				
	Adv.	ON / START / END / BOTH / OFF / EVENT, Output Signal 5V ,BNC type				
Display	4.3" TFT LCD					
Protection	OCP, OVP, OPP, OTP, LVP, RCP and FAN.					
Interface	Standard USB, PLC remote, LAN, Analog / Option GPIB, RS-232					
Eeciency (at Full load) ¹¹	≥ 74%	≥ 81%	≥ 84%	≥ 83%	≥ 84%	≥ 84%
Response Time (Tr/Tf) ¹²	275-400usec (Typical)					
Electromagnetic compatibility (EMC)	Complies with the requirements of the following directive and standards. EMC Directive 2014/30/EU EN 55011:2016/A1:2017 (Group 1, Class A), EN 61326-1:2013, EN 61326-2-1:2013, EN 61000-3-11:2000, EN 61000-3-12:2011					
Safety	Complies with the requirements of the following directive and standards. Low Voltage Directive 2014/30/EU, EN 61010-1					
Op. / Non-Op. Temp. / Humidity ¹³	0 to 40°C/-40 to 75°C/20 to 80%RH					
Dimension (W x H x D), mm	430 x 88 x 500	430 x 88 x 500	430 x 88 x 500	430 x 88 x 500	430 x 176 x 500	430 x 176 x 500
Weight	15KG	15KG	15KG	15KG	28KG	28KG
STANDARD ACCESSORIES						
Interlock Disable Key (1505)				X1		
USB Cable				X1		
Shorting bar				X1		
Power Cord (125Vac/10A)	X1	-				

Specifications subject to change