

VPAC-S 1-Phase AC Power Sources

250 – 10.000 VA



OVERVIEW

- AC / DC and AC + DC operation
- Simulation of single-phase networks
- 250 – 10.000 VA power output
- 0 – 700 VAC / 1.000 VDC output voltage
- 1 – 2.000 Hz variable frequency (sine, square, triangle)
- Currents up to 600 A
- Graphical Display
- Measuring of voltage, current, average and peak current, effective power, idle power, apparent power, power factor, crest factor
- Voltage and current constant mode
- Free memory space for programmable curve forms (WAV files), enabled over an external SD card (optional)
- 10 storage locations to save current configuration
- External oscillator input + / - 10 V with adjustable time delay up to 70 ms (optional)
- Galvanic isolated analogue interface: 0 – 5 V or 0 – 10 V (optional)
- Digital interface IEEE, RS232/485, USB, LAN (optional)
- Script control: process programming and booting from memory card
- Creation of user-defined curve shapes and programming via memory card or digital interface
- Three non-volatile curve shapes (programming via memory card)
- Datalog function: operation values can be saved in an adjustable interval to a memory card
- Script operation in combination with Datalog function allows an independent stand-alone test field setup
- Sync input synchronizes the device with external sources (optional)
- Sync output triggers external measurement instruments or similar (optional)
- Disengageable output voltage for a determined amount of half periods
- Connectable output voltage for a determined amount of time (optional)
- Special version on request

PRODUCT EXAMPLES

Type	Power VA	Current VAC / VDC	max. Current A	Dimensions
VPAC-S 250	250	0 – 300 / 0 – 425	0 – 3	19" x 4 HE x 434,5 mm
VPAC-S 500	500	0 – 300 / 0 – 425	0 – 6	19" x 4 HE x 434,5 mm
VPAC-S 1000	1.000	0 – 300 / 0 – 425	0 – 10	19" x 6 HE x 434,5 mm
VPAC-S 2000	2.000	0 – 300 / 0 – 425	0 – 15	19" x 6 HE x 434,5 mm
VPAC-S 3000	3.000	0 – 300 / 0 – 425	0 – 20	19" x 10 HE x 434,5 mm
VPAC-S 4000	4.000	0 – 300 / 0 – 425	0 – 30	19" x 16 HE x 600 mm
VPAC-S 5000	5.000	0 – 300 / 0 – 425	0 – 35	19" x 16 HE x 600 mm
VPAC-S 6000	6.000	0 – 300 / 0 – 425	0 – 40	19" x 16 HE x 600 mm
VPAC-S 7000	7.000	0 – 300 / 0 – 425	0 – 50	19" x 20 HE x 800 mm
VPAC-S 8000	8.000	0 – 300 / 0 – 425	0 – 60	19" x 20 HE x 800 mm
VPAC-S 9000	9.000	0 – 300 / 0 – 425	0 – 70	19" x 25 HE x 800 mm
VPAC-S 10000	10.000	0 – 300 / 0 – 425	0 – 80	19" x 25 HE x 800 mm

Subject to modification without notice, errors and omissions excepted

OPTIONS

Appendix	Description
..../230	Input 230 / 207 – 253 VAC
..../400	Input 400 / 360 – 440 VAC
..../3P208	Input 3 x 208 / 187 – 229 VAC
..../3P400	Input 3 x 400 / 360 – 440 VAC
..../3P480	Input 3 x 480 / 432 – 528 VAC
..../V500	Extended voltage range 0 – 500 VAC / 0 – 700 VDC -40 % I _{max}
..../V700	Extended voltage range 0 – 700 VAC / 0 – 1.000 VDC -50 % I _{max}
..../F1000	Extended frequency range 1 – 1.000 Hz
..../F2000	Extended frequency range 1 – 2.000 Hz
..../LT	Interface IEEE488
..../LTRS485	Interface RS485
..../LTRS232	Interface RS232
..../LAN	Interface LAN
..../USB	Interface USB
..../ATI 5	Isolated analogue interface 0 – 5 VDC set and monitor
..../ATI 10	Isolated analogue interface 0 – 10 VDC set and monitor
..../EXT/OSZ	OSZ external oscillator input
..../SD	SD card slot
..../SYNC A	Sync output for triggering external measurement devices or similar (optional)
..../SYNC E	Sync input for synchronization with external sources (optional)
..../INTLOCK	Interlock input / safety shutdown
..../DIP	Disengageable output voltage during a specific number of half periods (digital interface required)
..../GATE	Engageable output voltage during a specific amount of time (digital interface required)
..../APuls	Adjustable puls sequence (digital interface required)
..../LoadR	Load reverse energy recovery
..../LoadLR	Load energy recovery / regeneration in development

TECHNICAL DATAS

Input Voltage Specification

Input voltage range	230 VAC / 400 VAC / 3 x 208 VAC / 3 x 400 VAC / 3 x 480 VAC ±10 %
Input frequency	47 – 63 Hz

Output Specifications

Grid regulation	0,10 %
Load control	0,10 %
Distortion Pmax	0,10 %
Programming accuracy	100 mV
AC voltage	
Programming accuracy	100 mV
DC voltage	
Programming accuracy < 10 A	1 mA
Effective constant current > =10 A	10 mA
Programming accuracy	0,1°
Activation phase	
Programming accuracy	0,1 Hz
Frequency	
Frequency standard	0 – 500 Hz
External oscillator input	0 – 10 V / 1 kHz
Resolution, Measurement,	100 mV
Effective voltage,	
DC voltage,	
Peak voltage	
Resolution , Measurement <10 A	1 mA
Effective current, DC current	
Peak current > =10 A	10 mA
Resolution , Measurement < 10 A	10 mW
Active power > =10 A	100 mW

Programming & Controls

Output Control & Monitoring	Front panel and/or optional Analog 0 – +5V/+10V isolated / Digital 12 bit: RS232, RS485, IEEE488, LAN, USB, SD card
-----------------------------	--

Ambient Conditions

Cooling	Fans
Operating temperature	0 – 50°C
Storage temperature	-20 – 70°C
Humidity	< 80 %
Operating height	< 2.000 m
Weight	30 – 400 kg