



# 3310G Series DC Electronic Load

	Normal mode	Turbo mode
3310G	60V / 30A / 150W	60V / 60A / 300W
3311G	60V / 60A / 300W	60V / 120A / 600W
3312G	250V / 12A / 300W	250V / 24A / 600W
3314G	500V / 12A / 300W	500V / 24A / 600W
3315G	60V / 15A / 75W	60V / 30A / 150W
3316G	80V / 80A / 400W	80V / 160A / 800W
3318G	500V / 20A / 400W	500V / 40A / 800W



## Features

- 5 digital V / A / W Meter can be displayed on Large LCD display simultaneously.
- Flexible CC, CR, CV, CP, CC + CV, CP + CV, Dynamic and short circuit operation modes.
- Built-in test modes include Battery Discharge, BMS, Fuse/ Breaker Trip/Non-Trip, Short circuit, OCP, OPP test modes.
- Not only CC, CR, and CP mode have parallel operation functions, but CV mode also has parallel operation functions.
- Turbo mode can withstand up to 2 times the current and power electronic load within 2 sec. period , most fit Fuse/ Breaker and BMS , Short circuit , OCP , OPP test.
- Provide battery BMS protection test function.
- High Slew Rate : 3310G up to 5A/uS , 3311G up to 10A/uS , 3315G up to 2.5A/uS
- Support MPPT CC、CR、CV test function for solar panel.
- Short circuit duration can be set within short circuit test.
- Can set the power-on status value.
- Voltage meter display can be configured as polarity positive ("+" or negative ("-") .
- Synchronous parallel execution function ( SYNC. Load on )
- Can be configured in the Mainframe of 3302G (single channel) ~ 3305G (dual channels) or 3300G (Quad channels) , each mainframe has up to 150 sets Store/Recall memory.
- Optional programmable NTC Resistor (installed in mainframe)
- Optional Interface : GPIB ~ RS232 ~ USB ~ LAN.
- Protection against V, I, W, and °C.
- Optional 9923 load current waveform generator to provide the battery actual discharge current waveform simulation.

## Descriptions

- Each 3310G Series module has its own control and display panel, CC/CR/CV/CP/Dynamic modes, plug in 3302G/3305G/3300G mainframe with 150 sets Store/Recall memory which provides load set-up more efficiently, also can be controlled via RS232 ~ Ethernet ~ USB and GPIB interface .
- The new Turbo mode is designed for overload or protection testing, which includes OCP, OPP, Short for AC/DC or DC/DC power source; Over Charge/Discharge and Short for Battery BMS protection; and Blow/Not Blow testing for Fuse, Breaker or PTC Current Protection Components.
- Support Short, OCCP and OCDP protection tests for battery BMS protection testing, the peak current before protection and protection response time are measured.
- BMS, Fuse, OCP and OPP single-key test functions on the module make test more efficient.
- Dynamic can be simulated under CC, CP mode. The current Rise / Fall slew rate can be adjusted individually and there is an external signal input so that load can have a simulated Specific Load Current Waveform, optional 9923 Load Current Waveform Generator is able to support real current waveform testing.
- SHORT duration setting and SHORT\_VH, SHORT\_VL setting function, also can measure Short Voltage and Current.
- Programmable LOAD ON/OFF voltage, GO/NG meter check, Voltage meter display "+" or "-" is selectable and 150 sets Store / Recall larger memory is much advance feature for each different application.
- 150 sets test parameter and status storage function can call the storage memory real time in accordance with the auto sequence requirement , at any time to tune out the stored memory for use.

## Applications

- Voltage / Current source SMPS transient response
- Voltage Source Current limit testing and battery emulation for Charger testing
- Battery discharge capacity
- Lithium battery BMS charge and discharge protection
- Fuse , Breaker , PTC specification test
- MPPT test function for solar panels
- R&D, Quality Control
- ATE system
- Production testing

## Specifications

MODEL	3310G	3311G	3312G	3314G	3315G
Power	150W, 300W max. <sup>*1</sup>	300W, 600W max. <sup>*1</sup>	300W, 600W max. <sup>*1</sup>	300W, 600W max. <sup>*1</sup>	75W, 150W max. <sup>*1</sup>
Current	30A, 60A max. <sup>*1</sup>	60A, 120A max. <sup>*1</sup>	12A, 24A max. <sup>*1</sup>	12A / 24A max. <sup>*1</sup>	15A / 30A max. <sup>*1</sup>
Voltage	60V	60V	250V	500V	60V
Min. Operating Voltage	0.3V @ 30A	0.3V @ 60A	1V @ 12A	6V @ 12A	0.25V @ 15A
<b>PROTECTIONS</b>					
Over Power Protection(OPP)			105%		
Over Current Protection(OCP)			105%		
Over Voltage Protection(OVP)			105%		
Over Temp Protection(OTP)			YES		
<b>Constant Current Mode</b>					
Range <sup>*2</sup>	0 ~ 3A	0 ~ 30A	0 ~ 6A	0 ~ 60A	0 ~ 1.2A
Resolution	0.05mA	0.5mA	0.1mA	1mA	0.02mA
Accuracy					± 0.05% of (setting + Range)
<b>Constant Resistance Mode</b>					
Range	2~120KΩ	0.02Ω~2Ω	1Ω~60 KΩ	0.0083Ω~1Ω	25Ω~1500KΩ
Resolution	0.00833mS	0.033mΩ	0.0166mS	0.0166mΩ	0.0066mS
Accuracy					± 0.2% of (Setting + Range)
<b>Constant Voltage Mode</b>					
Range	0 ~ 6V	0 ~ 60V	0 ~ 6V	0 ~ 60V	0 ~ 250V
Resolution	0.0001V	0.001V	0.0001V	0.001V	0.001V
Accuracy					± 0.025% of (Setting + Range)
<b>Constant Power Mode</b>					
Range	0 ~ 15W	0 ~ 150W	0 ~ 30W	0 ~ 300W	0 ~ 30W
Resolution	0.00025W	0.0025W	0.0005W	0.005W	0.001W
Accuracy					± 0.1% of (Setting + Range)
<b>Constant Current + Constant Voltage Mode</b>					
Range	60V	30A	60V	60A	250V
Resolution	0.001V	0.5mA	0.001V	1mA	0.01V
Accuracy					± 1.0% of (Setting + Range)
<b>Constant Power + Constant VoltageMode</b>					
Range	60V	150W	60V	300W	250V
Resolution	0.001V	0.0025W	0.001V	0.005W	0.01V
Accuracy					± 1.0% of (Setting + Range)
<b>Short/OCP/OPP Test Function</b>					
Short Time	Turbo OFF			100ms~10 Sec. or Continue	
	Turbo ON <sup>*1</sup>			100~2000ms	
Meas. Accuracy				NA	
OCP Time (Tstep)	Turbo OFF			100mS	
	Turbo ON <sup>*1</sup>			20mS	
Meas. Accuracy				NA	
OPP Time (Tstep)	Turbo OFF			100mS	
	Turbo ON <sup>*1</sup>			20mS	
Meas. Accuracy				NA	
<b>BMS Test Mode</b> <sup>*3</sup>					
Short Time	Turbo OFF			0.05mS~10ms	
	Turbo ON <sup>*1</sup>			0.05mS~10ms	
Meas. Accuracy				±0.005mS	
OCP Time (Tstep)	Turbo OFF			0.05mS~10ms / 11~1000ms	
	Turbo ON <sup>*1</sup>			0.05mS~10ms / 11~1000ms	
Meas. Accuracy				±0.005mS / ±0.2mS	
<b>Fuse Test Mode</b> <sup>*4</sup>					
Trip & Non-Trip Time	Turbo OFF			r1 : 1~5999ms, r2 : 6~16383sec	
	Turbo ON <sup>*1</sup>			1~2000mS	
Meas. Accuracy				r1 : ±0.2mS(<200mS), ±20mS(>200mS), r2: ±0.5S	
Repeat Cycle				0~255	
<b>Surge Test Mode</b>					
Surge current	0~60A		0~120A		0~24A
Normal current	0~30A		0~60A		0~12A
Surge Time				10~2000ms	
Surge Step				1~5	
<b>MPPT Mode</b>					
Algorithm				P & O	
Load mode				CV	
P&O interval				1000ms ~ 60000ms	
<b>Dynamic Mode (50KHz)</b>					
<b>Timing</b>					
Thigh & Tlow				0.010~9.999 / 99.99 / 999.9 / 9999mS	
Resolution				0.001 / 0.01 / 0.1 / 1mS	
Slew rate	0.008~0.5A/uS	0.08~5A/uS	0.016~1A/uS	0.16~10A/uS	0.0008~0.05A/uS
Accuracy				0.008~0.5A/uS	0.0008~0.05A/uS
				0.008~0.5A/uS	0.004~0.25A/uS
				0.008~0.5A/uS	0.04~2.5A/uS
<b>Measurement</b>					
<b>Voltage Read Back</b>					
Range (5 Digital)	6V	60V	6V	60V	60V
Resolution	0.0001V	0.001V	0.0001V	0.001V	0.0001V
Accuracy				± 0.025% of (Reading + Range)	
<b>Current Read Back</b>					
Range (5 Digital)	3A	30A	6A	60A	1.2A
Resolution	0.0001A	0.001A	0.0001A	0.001A	0.0002A
Accuracy				± 0.05% of (Reading + Range)	
<b>Power Read Back</b>					
Range (5 Digital)	15W	150W	30W	300W	30W
Resolution	0.001W	0.01W	0.001W	0.01W	0.001W
Accuracy				± 0.1% of (Reading + Range)	
<b>Current Monitor</b>					
Accuracy				FULL SCALE 10V	
<b>Current Programming Input</b>					
Programmable Short				FULL SCALE 10V	
Load ON Voltage	0.1 ~ 25V		0.1 ~ 25V	0.2 ~ 50V	
Accuracy				1% of (Setting + Range)	
Load OFF Voltage	0 ~ 25V		0 ~ 25V	0 ~ 50V	
Accuracy				0.025% of (Setting + Range)	
Typical Short Resistance	0.0086 Ω		0.0043 Ω	0.08 Ω	
Maximum Short Current	30 A		60A	12A	
Dimension(HxWxD)				143 x 108 x 412 mm	
Operating Temperature <sup>*5</sup>				0 ~ 40°C	

\*1 : Up to 2 times rated current and power @1/3 voltage rating Turbo mode operation for Fuse, BMS, Short / OCP / OPP testing.

\*2 : CC Mode can be forced on Range II

\*3 : The BMS test function is mainly applied to the Short / OCP / OPP and OCDP tests of the battery BMS protection board.

\*4 : Fuse test function is mainly used for fuse and breaker testing

\*5 : The operating temperature range is 0~40°C, the accuracy of this specification is only applicable to 25°C±5°C

## Order Information

## DC Electronic Load

- ▶ 3310G 60V · 30A · 150W
- ▶ 3311G 60V · 60A · 300W
- ▶ 3312G 250V · 12A · 300W
- ▶ 3314G 500V · 12A · 300W
- ▶ 3315G 60V · 15A · 75W

## DC Electronic Load Mainframe

- 3302G (single channel mainframe)  
5.5kg / W160mm / H177mm / D452mm
- 3305G (two channels mainframe)  
7.5kg / W269mm / H177mm / D452mm
- 3300G (four channels mainframe)  
9.3kg / W440mm / H177mm / D445mm

Optional interface : ① GPIB Card ② RS232 Card ③ USB Card ④ LAN Card

Optional feature : NTC Simulator ① 10KΩ NTC(100~500KΩ) ② 100KΩ NTC(1000~5MΩ)  
3310G ▶ 5A/uS  
3311G ▶ 10A/uS  
3315G ▶ 2.5A/uS

## Specifications

MODEL	3316G		3318G	
Power	400W, 800W max. <sup>*1</sup>		400W, 800W max. <sup>*1</sup>	
Current	80A / 160A max. <sup>*1</sup>		20A / 40A max. <sup>*1</sup>	
Voltage	80V		500V	
Min. Operating Voltage	0.8V @ 80A		4V @ 20A	
<b>PROTECTIONS</b>				
Over Power Protection(OPP)		105%		
Over Current Protection(OCP)		105%		
Over Voltage Protection(OVP)		105%		
Over Temp Protection(OTP)		YES		
<b>Constant Current Mode</b>				
Range <sup>*2</sup>	0 ~ 8.04A	0 ~ 80.4A	0 ~ 2.04A	0 ~ 20.4A
Resolution	0.134mA	1.34mA	0.034mA	0.34mA
Accuracy	± 0.05% of (setting + Range)			
<b>Constant Resistance Mode</b>				
Range	1Ω ~ 60kΩ	0.0083Ω ~ 1Ω	30Ω ~ 1800kΩ	0.3Ω ~ 30Ω
Resolution	0.0166mS	0.0166mΩ	0.000555mS	0.5mΩ
Accuracy	± 0.2% of (Setting + Range)			
<b>Constant Voltage Mode</b>				
Range	0 ~ 8.04V	0 ~ 80.4V	60V	500V
Resolution	0.000134V	0.00134V	0.001V	0.01V
Accuracy	± 0.025% of (Setting + Range)			
<b>Constant Power Mode</b>				
Range	0 ~ 40.02W	0 ~ 400.2W	0 ~ 40.02W	0 ~ 400.2W
Resolution	0.667mW	6.67mW	0.667mW	6.67mW
Accuracy	± 0.1% of (Setting + Range)			
<b>Constant Current + Constant Voltage Mode</b>				
Range	80V	80A	500V	20A
Resolution	0.00134V	1.34mA	0.01V	0.34mA
Accuracy	± 1.0% of (Setting + Range)			
<b>Constant Power + Constant Voltage Mode</b>				
Range	80V	400W	500V	400W
Resolution	0.00134V	6.67mW	0.01V	6.67mW
Accuracy	± 1.0% of (Setting + Range)			
Maximum Current	Turbo OFF Turbo ON <sup>*1</sup>	80A 160A		20A 40A
Meas. Accuracy	± 3.0% of (Reading + Range)			
<b>Short/OCP/OPP Test Function</b>				
Short Time	Turbo OFF Turbo ON <sup>*1</sup>	100ms~10 Sec. or Continue 100~2000ms		
Meas. Accuracy		NA		
OCP Time (Tstep)	Turbo OFF Turbo ON <sup>*1</sup>	100mS 20mS		
Meas. Accuracy		NA		
OPP Time (Tstep)	Turbo OFF Turbo ON <sup>*1</sup>	100mS 20mS		
Meas. Accuracy		NA		
<b>BMS Test Mode</b> <sup>*3</sup>				
Short Time	Turbo OFF Turbo ON <sup>*1</sup>	0.05mS~10ms 0.05mS~10ms		
Meas. Accuracy		±0.005mS		
OCP Time (Tstep)	Turbo OFF Turbo ON <sup>*1</sup>	0.05mS~10ms / 11~1000ms 0.05mS~10ms / 11~1000ms		
Meas. Accuracy		±0.005mS / ±0.2ms		
<b>Fuse Test Mode</b> <sup>*4</sup>				
Trip & Non-Trip Time	Turbo OFF Turbo ON <sup>*1</sup>	r1 : 1~5999ms, r2 : 6~16383sec 1~2000mS		
Meas. Accuracy		r1 : ±0.2mS(<200mS), ±20mS(>200mS), r2: ±0.5S		
Repeat Cycle		0~255		
<b>Surge Test Mode</b>				
Surge current		0~160A		0~40A
Normal current		0~80A		0~20A
Surge Time		10~2000ms		
Surge Step		1~5		
<b>MPPT Mode</b>				
Algorithm		P&O		
Load mode		CV		
<b>Dynamic Mode (50KHz)</b>				
<b>Timing</b>				
Thigh & Tlow		0.010~9.999 / 99.99 / 999.9 / 9999mS		
Resolution		0.001 / 0.01 / 0.1 / 1mS		
Slew rate	5.4 ~ 337.5mA/us	54 ~ 3375mA/us	1.28 ~ 80mA/us	12.8 ~ 800mA/us
Accuracy		± (5% of Setting) ±10μs		
<b>Measurement</b>				
<b>Voltage Read Back</b>				
Range (5 Digital)	8.04V	80.4V	60V	500V
Resolution	0.000134V	0.00134V	0.001V	0.01V
Accuracy	± 0.025% of (Reading + Range)			
<b>Current Read Back</b>				
Range (5 Digital)	8.04A	80.4A	2.04A	20.4A
Resolution	0.000134A	0.00134A	0.000034A	0.00034A
Accuracy	± 0.05% of (Reading + Range)			
<b>Power Read Back</b>				
Range (5 Digital)	100W	400W	100W	400W
Resolution	0.001W	0.01W	0.001W	0.01W
Accuracy	± 0.1% of (Reading + Range)			
<b>Current Monitor</b>				
Accuracy		FULL SCALE 10V		
<b>Current Programming Input</b>				
Programmable Short		0.5% of (Setting + Range)		
Load ON Voltage	0.1 ~ 25V	FULL SCALE 10V		
Accuracy		BUILT-IN		
Load OFF Voltage	0 ~ 25V	1% of (Setting + Range)		
Accuracy		0~100V		
Typical Short Resistance	0.009Ω	0.025% of (Setting + Range)		
Maximum Short Current	80A		0.15Ω	20A
Dimension(HxWxD)		143 x 108 x 412 mm		
Operating Temperature <sup>*5</sup>		0 ~ 40°C		

\*1 : Up to 2 times rated current and power @1/3 voltage rating Turbo mode operation for Fuse, BMS, Short / OCP / OPP testing. \*4 : Fuse test function is mainly used for fuse and breaker testing

\*2 : CC Mode can be forced on Range II

\*3 : The BMS test function is mainly applied to the Short / OCP / OPP and OCDP tests of the battery BMS protection board.

\*5 : The operating temperature range is 0~40°C, the accuracy of this specification is only applicable to 25°C±5°C

## Order Information


## DC Electronic Load

- 3316G  
80V · 80A · 400W
- 3318G  
500V · 20A · 400W

## DC Electronic Load Mainframe

- 3302G  
(single channel mainframe)  
5.5kg / W160mm / H177mm / D452mm
- 3305G  
(two channels mainframe)  
7.5kg / W269mm / H177mm / D452mm
- 3300G  
(four channels mainframe)  
9.3kg / W440mm / H177mm / D445mm

Optional interface : ① GPIB Card ② RS232 Card ③ USB Card ④ LAN Card



Power vs temperature curve